

***e* TRUCK MATE**



eTRUCK MATE BROCHURE

TECHNICAL SPECIFICATIONS

Model		eTruckmate
Drive Type		4×2
Steering Wheel Position		RHD
Cabin		Single
The Width Of Body (mm)		1520
Max Speed (Km/h)		90
Max Climbing Ability (%)		25
Power Battery		
Battery Type		Lithium Iron Phosphate
Battery Capacity (kwh)		38.64
Endurance Mileage(Km)		280(NEDC)
Nominal Voltage (V)		309.12
Battery Structure		1 Box, Parallel 96 Strings
Battery Supplier		Contemporary Amparex Technology Co. Limited
Charging Type		CCS Type 2
Motor		
Motor Type		Permanent Magnet Synchronous Motor
Motor Model		FTTBP060A
Motor Power (Rated /Peak) (KW)		30/60
Motor Torque (Rated /Peak) (N.m)		100/220
Motor Rotate (Rated /Peak) (r/min)		2865/9000
Motor Supplier		Beiqi Foton Motor Co. Ltd
On- Board Charger		
Charging Power (KW)		6.6
Charging Voltage (V)		250-450V
AC Charging Current (A)		32
Charging Mode		DC/AC
Charging Time		DC:1.5h AC:7h
Dimension		
Chassis Dimensions (mm)		4670×1590×1860
Plate Dimensions (mm)		4880×1680×1945
Cargo Box Dimensions (mm)		3050×1560×1570
FOH/ROH (mm)		1075/1205
Wheel Base (mm)		2600
Wheel Track (mm)		1320/1410
Weight		
GVW (Kg)		2540
Curb Weigh-Chassis (Kg)		1200
Chassis		
Steering Type		Rack & Pinion Type
Braking System		Front Disc / Rear Drum
Front Axle		1T
Rear Axle/Ratio		2T/ Ratio : 10.5
Suspension		McPherson independant suspension/ Non Independant suspension Longitudinal steel plate spring cylindrical shock absorder
Tyre		175R14
ABS+EBD		●
Electric Door and Window		●
Central Locking		●
Front Fog Light		●
LED Daytime Running Light		●
Options		
Airconditioning		●
Mp5		●
Air Deflector		○
Leather Seats		○
Note : Standard : ● ; Optional : ○ ; Without : ×		

"Specs Subject To Change Without Prior Notice"